

# GS-150

## Product information

GS-150 is a synthetic hydrophilic, amorphous fumed silica. Its specific surface area is about 150 m<sup>2</sup>/g.

### Product Property

- ◆ Control rheology and thixotropy
- ◆ Reinforcement of silicone elastomer
- ◆ Improve free movement
- ◆ Anti-flow and anti-subsidence
- ◆ thickener

### Physical data

Physical and chemical properties	unit	value
Specific surface area	m <sup>2</sup> /g	150±20
pH (4% suspension)	-	3.7-4.7
Drying reduction (105°C, 2h)	wt.%	≤1.0
Reduction of burning (1000°C, 2h)	wt.%	≤1.0
SiO <sub>2</sub> content	wt.%	≥99.8
Bulk density	g/l	50

### Applications

- ◆ Unsaturated polyester resin
- ◆ Adhesive and sealant
- ◆ Printing ink
- ◆ Paint and coatings
- ◆ Food and cosmetics
- ◆ High temperature silicone rubber, liquid silicone rubber

### Packaging

- ◆ pallet with paper bag:  
10 kg/ bag

Important Disclaimer: This data material is provided in good faith and for reference only, and users should refer to these data and conditions of use for analysis and experimentation to confirm whether they are suitable for their purposes. Our company does not guarantee the problems that occur in the sale of this product and the use of specific working conditions, and does not bear any direct, indirect or accidental loss liability. If users encounter problems during use, they can contact our technical department, and we will provide you with all the help.